

PHENOMENAL AIRE

HIGH PERFORMANCE INDOOR AIR QUALITY TECHNOLOGY

SERIES

C6 PULSE

PRODUCT DATA SHEET




Duct-mounted Targeted Bipolar Pulsed Ionization (TBPI) system for commercial HVAC operations.

Pulsed. Tunable. Auto-cleaning. Close-to-space ion delivery.

SERIES C6 PULSE UNIT

Commercial duct-mounted platform powered by AEIRO.



Auto-cleaning

10 carbon fiber emitters

No scheduled replacement parts

CORE PERFORMANCE

6,000
CFM
AIRFLOW
CAPACITY


>2.0B
IONS/CC
COMBINED

<9W
POWER
CONSUMPTION

24V
AC/DC
STANDARD

TARGETED BIPOLAR PULSED IONIZATION

TBPI controls ion polarity and timing to manage ion output and reduce immediate positive/negative ion recombination near the emitter.



STANDARD FEATURES

- ✓ Pulsed ionization output
- ✓ Tunable ionization output*
- ✓ Wi-Fi controllable with subscription
- ✓ 2.4 GHz Wi-Fi (not compatible with 5 GHz)
- ✓ Auto-cleaning system
- ✓ 10 carbon fiber brush ionization emitters
- ✓ 3-year extended warranty included with monitoring subscription

APPLICATION PROFILE

Designed for duct mounting. Ideal for complex duct setups and zone systems downstream of a VAV box, where closer-to-space installation can improve useful ion density.

DUCT
MOUNT

VAV
ZONE

IAQ
MODE

TECHNICAL SPECIFICATIONS

Model:	Phenomenal Aire Series C6 Pulse	Frequency:	50/60 Hz
Airflow Capacity:	6,000 CFM (10,194 m ³ /h)	Wi-Fi:	2.4 GHz
Capacity Rating:	25 tons	Output Electrodes:	5 carbon fiber electrodes per polarity
Total Ion Output:	>2.0B ions/cc (combined)	Dimensions (Dia x L):	7 x 9.5 in (175 x 237.5 mm)
Temperature Range:	-20 to 140°F (-28.9 to 60°C)	Weight:	2.0 lbs (0.91 kg)
Humidity Range:	0–95% RH, non-condensing	Compliance:	FCC, RoHS, UL 867, UL 2998 Compliant, CARB**, Prop 65**
Input Voltage – Standard:	24VAC/DC	Electrical Approvals:	ETL, CAN/CSA
Input Voltage – Optional:	110–277VAC with power supply		
Power Consumption:	<9 watts		

** CARB / Prop 65 status pending AEIRO confirmation

CONTROL DEFAULT

General IAQ fail-safe: when Wi-Fi is not connected or monitoring subscription is inactive, the unit operates in General IAQ mode with equal positive/negative ion timing and fixed pulse delay. If power is lost, the unit resumes from the last commanded setting.

ENERGY SAVINGS / IAQP

The ASHRAE 62.1 Indoor Air Quality Procedure provides a project-specific pathway for evaluating outside-air rates. C6 Pulse + carbon filtration may be considered as part of an IAQP analysis, subject to appropriate engineering and application review. Installing AEIRO does not by itself authorize an outside-air reduction.



1507-A Turring Drive, P.O. Box 3118
Indian Trail, NC 28079

main: 888-505-2988
TopProductInnovations.com

PAPC6REV09172027